

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY,
UNDER CONTRACT DE-AC02-76CH03073


PPPL-3566
UC-70

PPPL-3566

**Mode Conversion Heating Scenarios
for the National Compact Stellarator Experiment**

R. Majeski, J.R. Wilson, and M. Zarnstorff

May 2001



**PRINCETON PLASMA PHYSICS LABORATORY
PRINCETON UNIVERSITY, PRINCETON, NEW JERSEY**

PPPL Reports Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Availability

This report is posted on the U.S. Department of Energy's Princeton Plasma Physics Laboratory Publications and Reports web site in Calendar Year 2001. The home page for PPPL Reports and Publications is: http://www.pppl.gov/pub_report/

DOE and DOE Contractors can obtain copies of this report from:

U.S. Department of Energy
Office of Scientific and Technical Information
DOE Technical Information Services (DTIS)
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401
Fax: (865) 576-5728
Email: reports@adonis.osti.gov

This report is available to the general public from:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: 1-800-553-6847 or
(703) 605-6000
Fax: (703) 321-8547
Internet: <http://www.ntis.gov/ordering.htm>

Mode Conversion Heating Scenarios for the National Compact Stellarator Experiment

R. Majeski, J. R. Wilson, and M. Zarnstorff

Princeton Plasma Physics Laboratory, Princeton, NJ 08543

Radio frequency heating scenarios for the National Compact Stellarator eXperiment (NCSX) are considered. The focus here is on mode conversion from the fast to the slow ion Bernstein wave as either an electron or "bulk" ion heating technique, using a high-field side launch to directly access the ion-ion hybrid layer. Modeling for the planned parameters of NCSX ($R_{ave} \sim 1.4$ m, $a_{ave} \sim 0.4$ m, $B_T(0) \sim 1.2-2$ T, $n_e(0) \sim 2-5 \times 10^{19}$ m⁻³, $T_e(0) \sim T_i(0) \sim 1-2$ keV) for mode conversion in D-H and D-³He plasmas is presented. Possible types of high-field side antennas are also briefly discussed.

Introduction

The National Compact Stellarator experiment (NCSX), a compact, quasi-axisymmetric stellarator (QAS), which is proposed for construction at the Princeton Plasma Physics Laboratory, has as one of its missions the exploration of high beta equilibria in the QAS configuration. These experiments will require high power RF heating at the 6 MW level, in addition to the baseline heating system - 6 MW of neutral beam injection. In order to make maximum use of existing facilities, a low frequency ($\sim 20-30$ MHz) heating scenario is desirable. Further constraints are imposed on the choice of a heating scenario by the use of hydrogen neutral beam injection, and a desire to avoid production of a fast ion tail. During the NCSX Physics Validation Review in March, 2001[1], a decision was reached to focus on mode conversion heating as the scenario of choice.

Mode Conversion Heating

Mode conversion heating was first successfully demonstrated using a high field side launch in the TFR tokamak [2]. Efficient, localized electron heating using mode conversion was demonstrated in TFTR [3], and more recently has been extensively utilized in C-MOD [4]. In tokamaks, a low field side launch of the fast wave in D-³He has now been most commonly employed. Mode conversion with a high field side launch, which is efficient with a wider variety of ion species mixes, has now been utilized successfully in stellarators, notably CHS [5]. Modeling of NCSX plasmas has indicated that a high field side fast wave launch is necessary to efficiently access the mode conversion surface. It appears possible that the present NCSX modular magnetic field coil design will permit installation of a high field side "comblane" antenna [6].

The METS 95 code, a 1-D hot plasma full-wave code which has been extensively benchmarked during mode conversion heating experiments in TFTR and C-MOD, has been employed to model mode conversion in NCSX. Mode conversion scenarios for NCSX have now been identified for D-H and D-³He plasmas. Either ion or electron

heating can be selected through an appropriate choice of the species mix, magnetic field, and launched wavenumber.

Mode conversion in D-H

The results of modeling D-H mode conversion are shown in Fig. 1 (a & b). Figure 1(a)




Figure 1. Dispersion relation for mode conversion in 10% H/90% D in NCSX (a), and power deposition profile (b). 82% of the launched power is deposited on electrons within the simulation window, with a full-width at half-max of ~ 15 cm. Central density for the simulation was $5 \times 10^{19} \text{ m}^{-3}$ (parabolic profile), central $T_e = T_i = 1$ keV, 1.6 T, with a launched frequency of 20 MHz and wavenumber of 9 m^{-1} .

is a plot of the dispersion relation for 10% H in a D majority plasma, with a central magnetic field of 1.6 T, a central electron density of $5 \times 10^{19} \text{ m}^{-3}$ (parabolic profile), for a fast wave excited on the high field side at 20 MHz with a wavenumber of 9 m^{-1} . As is well-known, a fast wave launched from the high field side has direct access to the IBW branch of the dispersion. Minimization of tunneling to the low field side of the mode conversion region is assured by choosing a wavenumber and species mix which results in a wide evanescent layer, as shown in Figure 1(a).

For the ion and electron temperatures chosen ($T_e=T_i= 1$ keV), METS 95 indicates that majority D/minority H mode conversion will produce relatively weak absorption, with a broad deposition profile on the electrons. Absorption occurs to the high field side of the hydrogen cyclotron layer, so that for near-axis electron absorption the Ω_H layer must be located well to the low field side of the axis. Still lower hydrogen concentrations ($\sim 5\%$) would allow experiments in conventional light ion minority heating, although fast ion tail populations are not expected to be well confined in NCSX.

Mode conversion in H-³He

The most promising and flexible ion system for mode conversion heating in NCSX is H - ³He, which should permit localized ion or electron heating (or electron current drive), either on or off axis. With a transmitter frequency of 20 MHz (the lowest practical frequency for the existing PPPL sources), on axis heating can be obtained at central magnetic fields as low as 1.3T. Localized electron heating can be produced in H-³He for a wide range of species mixes and wavenumbers. However, ion heating is predicted for low concentrations of either hydrogen (light ion minority) or helium (heavy ion minority). In Figure 2 (a - c) power deposition profiles for mode conversion in varying H-³He mixes are shown. Fig. 2(a) shows the results of METS 95 modeling for 10% H in




Figure 2. Power deposition profiles with increasing fractions of H in ³He for mode conversion at 20 MHz in NCSX. (a) Hydrogen heating, 12 m⁻¹, 10% H in ³He, 1.3T. (b) Electron heating, 6 m⁻¹, 25% (n_i/n_e) ³He in H, 1.5T. (c) ³He heating, 4 m⁻¹, 10% ³He in H, 1.8T.

³He. At high launched wavenumber (12 m⁻¹) ion heating is predicted. Ion tail formation will be lessened due to the high hydrogen concentration. If a lower launched wavenumber or a higher hydrogen concentration is chosen, then localized electron heating rather than ion heating is predicted. Note that the deposition profile is very narrow, with a FWHM of approximately 2 cm. 3D effects will likely broaden the deposition profile, but insofar as the mod-B surfaces lie on flux surfaces very narrow power deposition profiles are likely.

At higher ³He fractions electron heating is predicted to dominate, for a wide range of launched wavenumbers. In Figure 2(b) is shown the modeled power deposition profile for 25% ³He concentration, at 1.5T. 90% of the power is deposited on electrons. In Figure 2(c) a predicted deposition profile for 10% ³He in H is shown, at 1.8T. Deposition at large minor radius may be interesting here, since this case corresponds to IBW ion damping near a cyclotron resonance, which is desirable for rf shear flow generation. Operation at 1.5T would result in power deposition at r/a ~ 2/3. Note that the deposition layer (in this 1-D model) is very narrow, with a FWHM of about 1 cm.

These capabilities (localized or broad electron heating, localized current drive or current profile control, localized ion heating, possible rf shear flow drive) combine to make mode conversion heating an attractive physics tool for NCSX.

RF systems and antennas for mode conversion

As stated earlier, the most attractive antenna for a high field side launch in NCSX is probably the combline [6], which utilizes "passive" excitation of a wide array of current straps. In order to provide the required 6 MW of RF heating, three antennas could be installed in NCSX, on the high field side of the device, with each antenna centered about the "bullet" plasma cross section.

The existing PPPL FMIT units could be used for mode conversion in NCSX, in a time-sharing arrangement with NSTX. An engineering study has determined that operation of four of the FMIT sources over the frequency range of 20 - 30 MHz is feasible; this would provide 6-8 MW of rf source power. Although the sharing of sources precludes simultaneous RF heating of NSTX and NCSX, the transmitter modifications proposed would require minimal down time to change frequencies.

Conclusion

Modeling with a 1-D full wave code indicates that mode conversion heating is feasible for NCSX, provided the device design can accommodate a high-field side antenna.

Acknowledgements

This work was supported by USDoE contract DE-AC02-76-CH0-3073.

References

- [1] Proceedings of the NCSX review can be obtained at <http://www.pppl.gov/ncsx/pvr/pvr.html>
- [2] Equippe TFR, in Plasma Physics and Controlled Nuclear Fusion Research, Proc. 9th International Conf., Baltimore, 1982, Vol. 2, p. 17.
- [3] R. Majeski et al., Phys. Rev. Lett. 76, 764 (1996).
- [4] P. Bonoli et al., Phys. Plasmas 4, 1774 (1997).
- [5] T. Watari, Plasma Phys. Control. Fusion 40, A13 (1998).
- [6] C. P. Moeller et al., in Radio Frequency Power in Plasmas, Proc. 10th Top. Conf., Boston, 1993 (AIP Conf. Proc. Vol. 289), p. 323

External Distribution

Plasma Research Laboratory, Australian National University, Australia
Professor I.R. Jones, Flinders University, Australia
Professor João Canalle, Instituto de Fisica DEQ/IF - UERJ, Brazil
Mr. Gerson O. Ludwig, Instituto Nacional de Pesquisas, Brazil
Dr. P.H. Sakanaka, Instituto Fisica, Brazil
The Librarian, Culham Laboratory, England
Library, R61, Rutherford Appleton Laboratory, England
Mrs. S.A. Hutchinson, JET Library, England
Professor M.N. Bussac, Ecole Polytechnique, France
Librarian, Max-Planck-Institut für Plasmaphysik, Germany
Jolan Moldvai, Reports Library, MTA KFKI-ATKI, Hungary
Dr. P. Kaw, Institute for Plasma Research, India
Ms. P.J. Pathak, Librarian, Institute for Plasma Research, India
Ms. Clelia De Palo, Associazione EURATOM-ENEA, Italy
Dr. G. Grosso, Instituto di Fisica del Plasma, Italy
Librarian, Naka Fusion Research Establishment, JAERI, Japan
Library, Plasma Physics Laboratory, Kyoto University, Japan
Research Information Center, National Institute for Fusion Science, Japan
Dr. O. Mitarai, Kyushu Tokai University, Japan
Library, Academia Sinica, Institute of Plasma Physics, People's Republic of China
Shih-Tung Tsai, Institute of Physics, Chinese Academy of Sciences, People's Republic of China
Dr. S. Mirnov, TRINITI, Troitsk, Russian Federation, Russia
Dr. V.S. Strelkov, Kurchatov Institute, Russian Federation, Russia
Professor Peter Lukac, Katedra Fyziky Plazmy MFF UK, Mlynska dolina F-2, Komenskeho
Univerzita, SK-842 15 Bratislava, Slovakia
Dr. G.S. Lee, Korea Basic Science Institute, South Korea
Mr. Dennis Bruggink, Fusion Library, University of Wisconsin, USA
Institute for Plasma Research, University of Maryland, USA
Librarian, Fusion Energy Division, Oak Ridge National Laboratory, USA
Librarian, Institute of Fusion Studies, University of Texas, USA
Librarian, Magnetic Fusion Program, Lawrence Livermore National Laboratory, USA
Library, General Atomics, USA
Plasma Physics Group, Fusion Energy Research Program, University of California at San
Diego, USA
Plasma Physics Library, Columbia University, USA
Alkesh Punjabi, Center for Fusion Research and Training, Hampton University, USA
Dr. W.M. Stacey, Fusion Research Center, Georgia Institute of Technology, USA
Dr. John Willis, U.S. Department of Energy, Office of Fusion Energy Sciences, USA
Mr. Paul H. Wright, Indianapolis, Indiana, USA

The Princeton Plasma Physics Laboratory is operated
by Princeton University under contract
with the U.S. Department of Energy.

Information Services
Princeton Plasma Physics Laboratory
P.O. Box 451
Princeton, NJ 08543

Phone: 609-243-2750
Fax: 609-243-2751
e-mail: pppl_info@pppl.gov
Internet Address: <http://www.pppl.gov>