

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY,
UNDER CONTRACT DE-AC02-76CH03073

PPPL-3983
UC-70

PPPL-3983

**The H-mode Pedestal and Edge
Localized Modes in NSTX**

by

R. Maingi, E.D. Fredrickson, J.E. Menard,
N. Nishino, A.L. Roquemore, S.A. Sabbagh, K. Tritz,
and the NSTX Team

July 2004



**PRINCETON PLASMA PHYSICS LABORATORY
PRINCETON UNIVERSITY, PRINCETON, NEW JERSEY**

PPPL Reports Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Availability

This report is posted on the U.S. Department of Energy's Princeton Plasma Physics Laboratory Publications and Reports web site in Fiscal Year 2004. The home page for PPPL Reports and Publications is: http://www.pppl.gov/pub_report/

DOE and DOE Contractors can obtain copies of this report from:

U.S. Department of Energy
Office of Scientific and Technical Information
DOE Technical Information Services (DTIS)
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401

Fax: (865) 576-5728

Email: reports@adonis.osti.gov

This report is available to the general public from:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: 1-800-553-6847 or
(703) 605-6000

Fax: (703) 321-8547

Internet: <http://www.ntis.gov/ordering.htm>

The H-mode Pedestal and Edge Localized Modes in NSTX

R. Maingi^a, E.D. Fredrickson^b, J.E. Menard^b, N. Nishino^c, A.L. Roquemore^b, S.A. Sabbagh^d, K. Tritz^e, and the NSTX Team

^aOak Ridge National Laboratory, Oak Ridge TN, 37831, USA

^bPrinceton Plasma Physics Laboratory, Princeton, NJ 08543, USA

^cHiroshima University, Japan

^dColumbia University, New York, NY USA

^eJohns Hopkins University, Baltimore, MD USA

The research program of the National Spherical Torus Experiment (NSTX) routinely utilizes the H-mode confinement regime to test and extend beta and pulse length limits. As in conventional aspect ratio tokamaks, NSTX observes a variety of edge localized modes (ELMs) in H-mode. Hence a significant part of the research program is dedicated to ELMs studies.

Several different types of ELMs have been observed in NSTX, including Type I ELMs and Type III ELMs from conventional aspect ratio classifications, and also a new type, which has




Fig. 1 – discharge with mixed Type I and Type V ELMs. The dashed line indicates time of a Type I ELM. Type V ELMs are observed as the small periodic oscillations prior to the Type I ELM.

been labeled[1] as Type V. In NSTX, Type I ELMs are observed with heating power well above the L-H threshold, cause a typical decrease in the stored energy of 5-15%, have no clear electromagnetic pre-cursor, and often result in a cold pulse propagation from the edge into the core. A ‘giant’ version of the Type I ELM has been observed, which can reduce the stored energy by 30% under certain conditions. Type III ELMs cause a decrease in the stored energy of <2-3%, have a clear electromagnetic signature and a low frequency pre-cursor < 40 kHz, and are observed in discharges

with heating power close to the L-H threshold in certain shapes. Type V ELMs individually cause no measurable decrease in the stored energy, are observed over a wide range of heating power, and have a distinct n=1 mode electromagnetic signature/pre-cursor. These small ELMs can co-exist with Type I ELMs in certain cases.

An example of a mixed Type I/Type V ELM discharge is shown in Fig. 1 ($I_p=0.8$ MA, $B_t=0.45$ T, $P_{\text{NBI}}=6$ MW). Several small type V ELMs are observed on the D_{\square} (panel 1(b)) and ultra-soft X-rays (USXR - panels 1(c) and 1(d)) before the Type I ELM at ~ 0.349 sec. This particular type I ELM decreases the stored energy (W_{MHD}) by $\sim 15\%$. As can be seen in panels




Fig. 2 – discharge with mixed Type III ELMs. The dashed line indicates time of a single Type III ELM, but several others are observed within this time window,

contrast to the type I ELM, an inward cold pulse propagation is not observed on the USXR emission. Note also that there is a clear electromagnetic pre-cursor in the 0.2-40 kHz range in panel 2(e), prior to the mode signature in panel 2(f).

1(e) and 1(f), no clear pre-cursor of the Type I ELM is observed in the frequency range from 0.2-400 kHz; the mode itself is apparent in the raw (non-integrated) data with a growth time ~ 150 μ sec.

An example of a Type III ELM discharge is shown in Fig. 2. It is clear from panel 2(a) that the effect of each of these ELMs is smaller than the statistical error bars of $\pm 1.5\%$. Other Type III ELMs have reduced the stored energy by up to 3%. Panels 2(c) and 2(d) show a drop in the inner USXR data and an increase in the far edge chords, as observed also in the Type I ELM. In

A scaling of the type I ELM energy loss in NSTX was recently reported[2] and is summarized here. The Type I ELM energy loss fraction in that study ($\Delta W_{\text{MHD}}/W_{\text{MHD}}$) was up to 7%, and decreased with increasing line average density. The pedestal stored energy was obtained by fitting the electron pressure profile from Thomson Scattering with a modified hyperbolic tangent function, and using a standard relationship between the pedestal pressure and stored energy. The analysis indicated that the pedestal electron density was typically in the range of $3\text{-}5 \times 10^{19} \text{ m}^{-3}$ and pedestal electron temperature was in the 200-250 eV range. The pedestal stored




Fig. 3 – tangential view of the NSTX lower divertor region. The image region of the fast framing visible camera is indicated by the yellow box.

energy typically represented between 25-33% of the total stored energy, assuming equal ion and electron temperatures at the top of the pedestal. Thus, the peak pedestal energy loss fractions approached 25-30% for the largest of the Type I ELMs from the study. In certain low recycling regimes in lower-single null configuration, ‘giant’ ELMs were observed which caused a reduction up to 30% of the total stored energy, but these were replaced by Type V ELMs at higher density and fueling rates.

A visible camera capable of up to 40,500 frames per second was installed to view the lower divertor and X-point region during these ELMs. The approximate view of the NSTX divertor with the camera is shown in Fig. 3. The center stack itself is not observed, but for the configurations shown below, the outer strike point and inner separatrix are observed.

The fast camera was used to capture each of the ELM types discussed above. Fig. 4 shows relevant frames from the discharge with Type III ELMs in Fig. 2, and a type I ELM similar to the one in Fig. 3. The inner separatrix is observed as a curve from the lower left to upper right, and the outer strike point is the nearly horizontal arc near the bottom of the image. The top second frame shows the start of the magnetic perturbation, with multiple strike points observed on the outboard side. This splitting persisted for up to 10 frames ($\sim 250 \mu\text{sec}$), after which a blob of visible light was observed to travel down the inner separatrix (presumably from above) and form

a MARFE-like structure along the inner divertor leg, probably in the vicinity of the X-point. The presence of a MARFE is not unexpected because the inner strike point is nearly always detached[3] in NSTX. It is clear that the ELM heat pulse did not burn through this MARFE-like region. Instead the MARFE-like region dissipates approximately 100 frames (~ 2.5 msec) before the next Type III ELM, after which the process was repeated for each ELM. We speculate that the long-lived magnetic pre-cursor in Panel 2(e) affected the magnetic topology in a way that dissipated the MARFE-like structure. The fast camera images are similar for Type V ELMs, except that the MARFE-like structure did not dissipate between ELMs. However Type I ELMs




Fig. 4 – unfiltered fast camera images (contrast enhanced) at 40,500 frames per second during one type III ELM for #112164 (upper set) and one Type I ELM for #112503 (lower set). Frame numbers are indicated.

clearly burned through the MARFE-like region all the way to the target (Fig. 4 – bottom row). The

MARFE-like structure was rebuilt on the order of tens of msec. Note that the total light during the Type I ELM was much brighter than the Type III.

In summary, we have presented examples of different ELM types in NSTX. This research was supported by US D.O.E. contracts DE-AC05-00OR22725, DE-AC02-76CH03073, W-7405-ENG-36, and grants DE-FG02-99ER54524, DE-FG02-99ER54519 and DE-FG02-99ER54523.

References

- [1] R. Maingi, et. al., “Observation of a High Performance Mode with Small ELMs in NSTX”, submitted to *Phys. Rev. Letts.*, 5/04.
- [2] R. Maingi, et. al., “ELMs and the H-mode Pedestal in NSTX”, submitted to *J. Nucl. Mater.*, 5/04.
- [3] V.A. Soukhanovskii, et. al., “Analyses of Divertor Regimes in NSTX”, submitted to *J. Nucl. Mater.*, 5/04.

External Distribution

Plasma Research Laboratory, Australian National University, Australia
Professor I.R. Jones, Flinders University, Australia
Professor João Canalle, Instituto de Fisica DEQ/IF - UERJ, Brazil
Mr. Gerson O. Ludwig, Instituto Nacional de Pesquisas, Brazil
Dr. P.H. Sakanaka, Instituto Fisica, Brazil
The Librarian, Culham Laboratory, England
Mrs. S.A. Hutchinson, JET Library, England
Professor M.N. Bussac, Ecole Polytechnique, France
Librarian, Max-Planck-Institut für Plasmaphysik, Germany
Jolan Moldvai, Reports Library, Hungarian Academy of Sciences, Central Research Institute
for Physics, Hungary
Dr. P. Kaw, Institute for Plasma Research, India
Ms. P.J. Pathak, Librarian, Institute for Plasma Research, India
Ms. Clelia De Palo, Associazione EURATOM-ENEA, Italy
Dr. G. Grosso, Instituto di Fisica del Plasma, Italy
Librarian, Naka Fusion Research Establishment, JAERI, Japan
Library, Laboratory for Complex Energy Processes, Institute for Advanced Study,
Kyoto University, Japan
Research Information Center, National Institute for Fusion Science, Japan
Dr. O. Mitarai, Kyushu Tokai University, Japan
Dr. Jiengang Li, Institute of Plasma Physics, Chinese Academy of Sciences,
People's Republic of China
Professor Yuping Huo, School of Physical Science and Technology, People's Republic of China
Library, Academia Sinica, Institute of Plasma Physics, People's Republic of China
Librarian, Institute of Physics, Chinese Academy of Sciences, People's Republic of China
Dr. S. Mirnov, TRINITI, Troitsk, Russian Federation, Russia
Dr. V.S. Strelkov, Kurchatov Institute, Russian Federation, Russia
Professor Peter Lukac, Katedra Fyziky Plazmy MFF UK, Mlynska dolina F-2,
Komenskeho Univerzita, SK-842 15 Bratislava, Slovakia
Dr. G.S. Lee, Korea Basic Science Institute, South Korea
Institute for Plasma Research, University of Maryland, USA
Librarian, Fusion Energy Division, Oak Ridge National Laboratory, USA
Librarian, Institute of Fusion Studies, University of Texas, USA
Librarian, Magnetic Fusion Program, Lawrence Livermore National Laboratory, USA
Library, General Atomics, USA
Plasma Physics Group, Fusion Energy Research Program, University of California
at San Diego, USA
Plasma Physics Library, Columbia University, USA
Alkesh Punjabi, Center for Fusion Research and Training, Hampton University, USA
Dr. W.M. Stacey, Fusion Research Center, Georgia Institute of Technology, USA
Dr. John Willis, U.S. Department of Energy, Office of Fusion Energy Sciences, USA
Mr. Paul H. Wright, Indianapolis, Indiana, USA

The Princeton Plasma Physics Laboratory is operated
by Princeton University under contract
with the U.S. Department of Energy.

Information Services
Princeton Plasma Physics Laboratory
P.O. Box 451
Princeton, NJ 08543

Phone: 609-243-2750
Fax: 609-243-2751
e-mail: pppl_info@pppl.gov
Internet Address: <http://www.pppl.gov>