PPPL-5238

Phase coherence of parametric decay modes during high-harmonic fast-wave heating in the National Spherical Torus Experiment

J. A. Carlsson, J. R. Wilson, J. C. Hosea, N. L. Greenough, and R. J. Perkins

February 2016



Prepared for the U.S. Department of Energy under Contract DE-AC02-09CH11466.

Full Legal Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Trademark Disclaimer

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

PPPL Report Availability

Princeton Plasma Physics Laboratory:

http://www.pppl.gov/techreports.cfm

Office of Scientific and Technical Information (OSTI):

http://www.osti.gov/scitech/

Related Links:

U.S. Department of Energy

U.S. Department of Energy Office of Science

U.S. Department of Energy Office of Fusion Energy Sciences

Phase coherence of parametric decay modes during high-harmonic fast-wave heating in the National Spherical Torus Experiment

J. A. Carlsson,^{1, a)} J. R. Wilson,¹ J. C. Hosea,¹ N. L. Greenough,¹ and R. J. Perkins¹ Princeton Plasma Physics Laboratory, Princeton University, Princeton, NJ 08543-0451, USA

(Dated: 29 February 2016)

Third-order spectral analysis, in particular the auto bicoherence, was applied to probe signals from high-harmonic fast-wave heating experiments in the National Spherical Torus Experiment. Strong evidence was found for parametric decay of the 30 MHz radio-frequency (RF) pump wave, with a low-frequency daughter wave at 2.7 MHz, the local majority-ion cyclotron frequency. The primary decay modes have auto bicoherence values around 0.85, very close to the theoretical value of one, which corresponds to total phase coherence with the pump wave. The threshold RF pump power for onset of parametric decay was found to be between 200 kW and 400 kW.

PACS numbers: 52.35.Mw, 52.35.Hr, 52.50.Qt

^{a)}carlsson@pppl.gov; Crow Radio and Plasma Science

I. INTRODUCTION

High-harmonic fast-wave (HHFW) heating is a heating scheme developed for high-beta tokamaks¹ and is used at the National Spherical Torus eXperiment $(NSTX)^{2-4}$ and Tokyo Spherical Tokamak-2 $(TST-2)^5$. The HHFW is susceptible to parametric decay instability $(PDI)^6$, where the HHFW pump wave decays into a low-frequency daughter wave and associated sidebands. The low-frequency daughter wave is typically an ion-cyclotron quasi mode (ICQM) and the sidebands either fast waves (FWs) or ion Bernstein waves $(IBWs)^6$. The intended absorption mechanism for HHFW heating is Landau damping on hot electrons in the plasma core. PDI is undesirable because it can create a parasitic absorption channel, where power is lost in the edge plasma.

As for any three-wave resonance, the three PDI modes must conserve energy and momentum:

$$f_0 = f_1 + f_2, \ \mathbf{k}_0 = \mathbf{k}_1 + \mathbf{k}_2, \tag{1}$$

respectively, where f is the frequency and \mathbf{k} is the wave vector. The subscript 0 is for the pump wave, and 1 and 2 for the low-frequency and sideband waves, respectively. Secondorder spectral analysis, typically the power spectral density, can be used to calculate the amplitude and frequency of plasma modes from probe signals. Frequency matching can then be used to tentatively identify PDI daughter waves. However, frequency matching alone could be accidental, especially in the presence of many modes. If the plasma parameters at the probe location are sufficiently well known, the dispersion relation can be used to calculate the wave vectors from the frequencies to determine whether Eq. (1) is satisfied.

If the wave vectors are not known, phase correlation can instead be used identify waves related by three-wave resonance⁷, including PDI pump and daughter waves. Unlike the power spectral density, third-order spectral analysis tools retain phase information and are therefore, in principle, capable of detecting phase correlation.

Two signals $X_a(t)$ and $X_b(t)$, e.g. time traces from probes in a plasma experiment, have correlation

$$C_1(t_1) = \langle X_a(t)X_b(t+t_1) \rangle \quad , \tag{2}$$

where the brackets denote averaging over time t. For two different signals, Eq. (2) is called the cross correlation. For the same signal, $X(t) = X_a(t) = X_b(t)$, it is called the auto correlation. The Fourier transform of the auto correlation is the power spectral density, or power spectrum for short. The power spectrum shows power (amplitude squared) as a function of frequency, but has no phase information. For some applications, such as PDI, the phase contains vital information, making the power spectrum an insufficient analysis tool. For such cases, the second-order power spectrum can be complemented by higherorder spectral-analysis tools. A common choice is the third-order bispectrum, the Fourier transform of the bicorrelation

$$C_2(t_1, t_2) = \langle X_a(t) X_b(t+t_1) X_b(t+t_2) \rangle , \qquad (3)$$

where the signals can again be either different (cross bicorrelation) or identical (auto bicorrelation). From the convolution theorem applied to Eq. (3) we get the following expression for the bispectrum:

$$B(f_1, f_2) = \hat{X}_a^*(f_1 + f_2)\hat{X}_b(f_1)\hat{X}_b(f_2) , \qquad (4)$$

where the star superscript denotes complex conjugation.

The value of the bispectrum depends not only on the degree of phase correlation, but also on the amplitude of the Fourier modes. The bicoherence $b(f_1, f_2)$ is a normalized version of the bispectrum that is amplitude independent⁷:

$$b^{2}(f_{1}, f_{2}) = \frac{|\langle B(f_{1}, f_{2}) \rangle|^{2}}{\left\langle |\hat{X}_{a}(f_{1} + f_{2})|^{2} \right\rangle \left\langle |\hat{X}_{b}(f_{1})\hat{X}_{b}(f_{2})|^{2} \right\rangle} , \qquad (5)$$

where the normalization is such that $0 \le b^2 \le 1$. $b^2(f_1, f_2) = 0$ when modes with frequencies f_1 and f_2 have completely uncorrelated phases, and $b^2(f_1, f_2) = 1$ when they are completely phase correlated. As discussed by Lagoutte⁸, the bispectrum is more robust with respect to low signal-to-noise ratio (S/N), but can give false positives, i.e., have large values even without phase correlation. The bicoherence, on the other hand, can give false negatives for phase-correlated signals with low S/N.

The auto bicoherence squared, from Eq. (5) or variants thereof, have been used to identify three-wave resonances in a wide range of plasma types, including low-temperature plasmas⁷, ionospheric/magnetospheric plasma⁸, the H-1 heliac⁹, the HT-7^{10,11}, JFT-2M^{12,13}, NSTX^{14,15} and TEXTOR¹⁶ tokamaks. For these previous applications, the frequency range was kHz to hundreds of kHz (sub kHz for space plasmas). The maximal bicoherence values found were in the range 0.2–0.8. To the best of our knowledge, the results presented in this paper are the first in the MHz to tens of MHz frequency range for a magnetic-fusion device, as well as the first use of third-order spectral analysis for identifying parametric decay. The peak bicoherence values achieved are as large as 0.87, more than a factor of four above the background noise.

In Section II we present results of second- and third-order spectral analysis of probe data from NSTX HHFW heating experiments and in Section III we summarize our findings.

II. RESULTS

The main purpose of the research presented in this paper was to investigate the usefulness of bicoherence for identifying parametric decay instability in magnetized fusion plasmas, in particular during HHFW heating in NSTX. A limited set of probe data (from NSTX shots 130595-130608, 130610-130616, 130618-130622) was analyzed using both second- and thirdorder spectral-analysis techniques. A comprehensive re-analysis of the full NSTX HHFWheating data set was beyond the scope of the project, but is currently underway as part of a separate effort and will be reported elsewhere when completed.

The studied shots combine varying levels of HHFW heating, up to 2.5 MW, with 2 MW of neutral-beam injection (NBI). The plasma current was 1 MA for all shots. The on-axis magnetic field was 0.5 T, giving a cyclotron frequency of 3.8 MHz for the majority deuterium ions. At the plasma edge in the outboard midplane the cyclotron frequency is reduced to 2.7 MHz.

Each of the analyzed shots has data from five different probes: F-G_mid, J-mid, J-top, Reflect and Edge. The richest data was found to be in F-G_mid, which is also the only probe with high enough S/N to compute the auto bicoherence. J-mid and J-top (and Reflect) each have similar signals, consistent with F-G_mid, but with lower S/N. The signal from the Edge probe is not discernible from noise. The F-G_mid and J-mid probes are located in the outboard midplane. The former between the two central antenna straps and the latter at a toroidal location some distance away from the antenna. Because only one signal from each shot had a sufficiently low S/N, the cross bicoherence between two signals was not computed. The sampling rate was 10⁸ samples per second, giving a Nyquist frequency of 50 MHz. An anti-alias filter had been used with roll-off starting at 40 MHz. The F-G_mid signals have 33 million samples each, J-mid and J-top have 31 million, and Reflect and Edge have 30 million. The signals were transformed from time to frequency domain using



FIG. 1. Spectrogram of shot 130608 F-G_mid probe signal (a), compared to snapshot of power spectrum at 326 ms (b). 2 MW of 30 MHz RF heating is turned on at 250 ms.

the Fast Fourier Transform (FFT). For the second-order spectral analysis, spectrograms (power spectral density vs. time) were computed, initially using a large window size of 1 ms (10^5 samples) for the FFTs, giving a very high frequency resolution of 1 kHz, but a noisy power spectrum. After an initial data analysis showed that a coarser frequency resolution of 100 kHz would suffice, the FFT window size was decreased to 10^3 samples and the results from 100 consecutive FFTs were averaged to maintain the 1 ms temporal resolution. This averaging increased the range of detectable signals by almost 10 dB to close to 50 dB, just a few dB below the theoretical limit of about 53 dB set by the quantization error for 16-bit digitization. A -20 dB notch filter at the 30 MHz RF frequency installed before the digitizer could allow even weaker signals to be detected. No other basic signal processing was found to be needed.

For all of the shots analyzed, the NBI was turned on at 75 ms or 150 ms, before the RF, which was turned on after 250 ms.

An example of the power spectrum of a probe signal during RF heating is shown in Fig. 1. It is evident from the spectrogram in Fig. 1a that 30 MHz RF heating was turned on at 250 ms and it seems that sidebands (one upper and two lower) and a low-frequency mode



FIG. 2. Power spectral density for the shot 130608 F-G_mid probe signal, averaged over the full, 80 ms RF-heating period. The statistically significant modes are labeled from a to k.

appear after about 5 ms, consistent with parametric decay of the RF pump wave. The frequencies match up, with an approximately 2.7 MHz low-frequency mode and upper and lower sidebands at around 30 ± 2.7 MHz. A second, lower sideband at 24.6 MHz can also be seen in the spectrogram. A completely stable, very narrow-bandwidth signal at exactly 5 MHz is present even before the RF was turned on. It is believed to be an artifact of the signal-digitizing process as implemented by the particular analog-to-digital converter that was used.

To minimize the noise of the power spectrum, the signal was averaged over the full RFheating period (250–330 ms). This average is thus computed using 8,000 FFTs on a total of 8 million signal samples. For the given spectral resolution of 0.1 MHz, this procedure should give the maximal S/N. The detectable range for signals was increased accordingly by a few dB to about 51.5 dB, just 2 dB below the theoretical limit for 16-bit digitization. The result is shown in Fig. 2. As can be seen, the noise is significantly reduced compared to the power spectrum shown in Fig. 1b, which was averaged over a single millisecond. In addition to the



FIG. 3. Auto bicoherence squared for the shot 130608 F-G_mid probe signal, averaged over the full, 80 ms RF-heating period

modes seen and discussed previously (labeled a, b, f, g, h and i in Fig. 2), some additional lower-amplitude modes become visible after maximal time averaging, including a second, upper side band at 35.4 MHz (j) and another low-frequency mode at 5.4 MHz (c).

An inherent limitation of the power spectrum is that it only contains information on the frequency and amplitude of the Fourier modes of a signal. The only way to determine if modes are related is to see if their frequencies match up. However, a frequency match alone is not conclusive, since it could be accidental. As will be shown next, third-order spectral analysis (the auto bicoherence in particular) provides a very useful complement, since it gives the phase correlation between modes, a direct measure of their interrelation.

The auto bicoherence squared, $b^2(f_1, f_2)$ as given by Eq. (5), was computed for the shot 130608 F-G_mid probe signal, again using the maximal time averaging, as described above. The result is shown in Fig. 3. The most notable feature of the contour plot in Fig. 3 is that it has several symmetries and the prominence of the lines $f_1 = \pm 30MHz$, $f_2 = \pm 30MHz$ and $f_1 + f_2 = \pm 30MHz$. To detect parametric decay, phase correlation with the pump



FIG. 4. In green, the auto bicoherence squared for the shot 130608 F-G_mid probe signal along the line indicated by an arrow in Fig. 3. In blue, the corresponding power spectral density from Fig. 2.

wave is of primary importance. To filter out redundant and less interesting information, we therefore look more closely at $b^2(f_1, f_2 = -30MHz)$, along the line indicated by the arrow in Fig. 3. The result is shown as the green graph in Fig. 4. To more easily determine the phase correlation of the modes identified in Fig. 2, the power spectrum, in blue, is plotted over the auto bicoherence squared in Fig. 4. It is confirmed that the suspected primary decay waves a (2.7 MHz), g (27.3 MHz) and i (32.7 MHz) are indeed products of parametric decay of the RF pump wave, with peak values of auto bicoherence squared of $b^2(f_1 = 2.7MHz, f_2 = -30MHz) = 0.74 = 0.86^2, b^2(f_1 = 27.2MHz, f_2 = -30MHz) =$ $0.75 = 0.87^2$ and $b^2(f_1 = 32.8MHz, f_2 = -30MHz) = 0.68 = 0.83^2$, respectively. The peak locations are sometimes slightly different for power spectrum and bicoherence, respectively, but the variation is within the frequency resolution of 0.1 MHz. The un-squared values of the auto bicoherence for the primary decay modes, in the range 0.85 ± 0.02 , are very close to the theoretical value of one for perfect phase correlation with the pump wave. A noisy



FIG. 5. Close up of low-frequency part of Fig. 4. The thin, black, vertical lines show fits of the mode frequency based on both power spectrum and bicoherence (2.7 MHz for mode a and 5.4 MHz for mode c, respectively).

signal is known to cause a bicoherence that underestimates the true phase correlation and Lagoutte recommends computing the bicoherence averaged over at least several hundred FFTs⁸. The close-to-ideal bicoherence values achieved here is most likely due to averaging over a substantially larger number (8,000) of FFTs.

The modes b and c are quite close together, to better separate them, only the lowfrequency parts of the auto bicoherence squared and power spectral density are plotted in Fig. 5. As can be seen, mode c is also relatively strongly phase correlated with the RF pump wave (mode h), with the auto bicoherence having a value of 0.74 [$b^2(f_1 = 5.5MHz, f_2 =$ $-30MHz) = 0.55 = 0.74^2$]. As was discussed previously, mode b is probably spurious and definitely not involved in the parametric decay with an auto bicoherence value of only 0.21 [$b^2(f_1 = 5.0MHz, f_2 = -30MHz) = 0.04 = 0.21^2$].

Similarly, the bicoherence and power-spectrum graphs are plotted for the sidebandfrequency range in Fig. 6. The modes f and j can be identified as secondary lower and



FIG. 6. Close up of the sideband-frequency range of Fig. 4. The thin, black, vertical lines shows mode-frequency fits (24.6 MHz, 27.3 MHz, 32.7 MHz and 35.4 MHz for modes f, g, i and j, respectively).

upper sidebands. Mode f has an auto bicoherence value of 0.75 $[b^2(f_1 = 24.5MHz, f_2 = -30MHz) = 0.56 = 0.75^2]$, virtually identical to that of its sister mode c. Mode j has an auto bicoherence value of 0.56 $[b^2(f_1 = 35.4MHz, f_2 = -30MHz) = 0.32 = 0.56^2]$, which is lower than the other daughter waves, but still statistically significant.

Returning to Fig. 4, of the three remaining modes that were labeled in Fig. 2, neither one has a bicoherence value above the noise level. Mode k has a frequency of exactly 40 MHz, which is where the anti-alias filter roll off begins, and might be an artifact of the filtering process. Modes d and e have broad peaks centered at 8.4 MHz and 16.8 MHz, respectively. Their lack of phase correlation with the RF pump wave indicates that they are not involved in the parametric decay, but their exact nature is currently unknown.

Several other shots yield very similar results, e.g. shot 130621, as shown in Fig. 7. The main difference from shot 130608 is that the background signal for shot 130621 is about 10 dB stronger, strong enough to entirely drown out the spurious mode k. Mode j, the



FIG. 7. Shot 130621 F-G_mid probe signal spectrogram (a) and auto bicoherence squared $b^2(f_1, f_2 = -30MHz)$ in green with power spectrum in blue (b)

secondary upper sideband, is also only barely discernible.

There is thus ample evidence that parametric decay of the 30 MHz RF pump wave occurs in the studied set of shots with a primary low-frequency mode that is always at 2.7 MHz, an exact match for the local majority-ion cyclotron frequency.

The one possible exception seen in the data set studied here is a brief, 2.5 ms period of shot 130597, as can be seen in Fig. 8. Between 260 and 262.5 ms the RF power is dropped from about 5 dB to -9 dB (see Fig. 8a) and the pump wave at 30 MHz splits into three additional modes: 1.1 MHz and 30.0 ± 1.1 MHz, as is shown in Fig. 8b. However, the S/N of the probe signal is too low for the auto bicoherence to confirm phase correlation and PDI in this case.

For all the shots where data were available (except 130622), the RF power is turned on after 250 ms. In some cases the RF power is held fairly constant for the 80 ms until the probe-signal sampling ends. In other cases, the RF power level is changed several times during the period 250–330 ms. Some examples from this latter category are shown in Fig. 9. The threshold power for onset of PDI could in principle be estimated from these cases from above by finding the smallest RF power level that causes PDI, and from below by finding the largest RF power level that does not cause PDI. For this analysis we will define presence of PDI as when the primary low-frequency mode and sidebands are all visible in the spectrograms (in addition to the RF pump wave). With this definition, PDI occurs for shot 130595 only briefly after 300 ms, as can be seen in Fig. 9b. The power spectral density of the probe signal at 30 MHz (assumed to be proportional to the RF power) during this brief burst of PDI activity reaches almost 20 dB, as seen in Fig. 9a. Analysing all the similar shots, we arrive at an estimate of the threshold power of 13–16 dB. There seems to be some variability between shots. Compare Figs. 9c and d with e and f, respectively. For the former, clear PDI occurs from 287–301 ms at a power of about 13 dB, whereas for the latter there is no PDI yet even at a power level of about 16 dB. The maximum power seen in any of the analyzed signal is about 24 dB (not shown), which corresponds to 2.5 MW. Due to the slight variability between shots, the best estimate of the threshold power is thus between 8% (-11 dB) and 16% (-8 dB) of full power, i.e., in the range of 200 kW to 400 kW.



FIG. 8. Shot 130597 power spectral density at 30 MHz vs. time on top (a) and corresponding spectrogram below (b). The circled areas show parametric decay into a lower-frequency daughter wave at 1.1 MHz.



FIG. 9. Shots 130595, 130601 and 130610. Power spectral density at 30 MHz vs. time on top (a, c, e) and corresponding spectrograms below (b, d, f).

III. CONCLUSIONS

Third-order spectral analysis was performed on a set of NSTX probe data from HHFWheating shots, collected on a single day. Bicoherence values in the range 0.85 ± 0.02 provides strong evidence of phase correlation through parametric decay of the 30 MHz RF pump wave into a low-frequency mode at 2.7 MHz and a 27.3 MHz lower and 32.7 MHz upper sideband. Somewhat lower bicoherence values of 0.74 and 0.75, respectively, for secondary 5.4 MHz low-frequency and 24.6 MHz lower-sideband modes strongly indicate that they also are PDI daughter waves. A 35.4 MHz secondary upper sideband can also be identified, with a bicoherence value of 0.56, about a factor of 2.5 above the noise floor. Second-order spectral analysis, in the form of a spectrogram of the power spectrum, shows that the onset of PDI occurs about 5 ms after the RF is turned on. The threshold RF power for onset of parametric decay was estimated to be between 200 kW and 400 kW (Fig. 9). A spectrogram with 1 ms temporal resolution allowed us to identify a brief (2.5 ms) occurrence of parametric decay into a 1.1 MHz low-frequency mode and 28.9 MHz lower and 31.1 MHz upper sidebands (Fig. 8). The bicoherence thus proved to be a valuable complement to the power spectral density for this data set, because some necessary requirements were met. To avoid false negatives, i.e. bicoherence values much less than unity despite phase correlation, a large set of samples with high S/N is needed. By tolerating a relatively coarse frequency resolution of 100 kHz, FFTs could be performed on small subsets of 1,000 samples at a time. The total sample set from the 80 ms RF heating period then resulted in 8,000 FFTs over which to average the bicoherence. This extensive averaging is the primary reason bicoherence values came so close to the ideal value of one for the phase-correlated modes. In contrast, the 2.5 ms episode during shot 130597 of PDI with a 1.1 MHz low-frequency daughter wave, with primary sidebands, only produced 250 FFTs resulting in a bicoherence that was indistinguishable from noise (not shown).

PDI is a particularly suitable target for bicoherence analysis because the pump frequency is known, effectively making the bicoherence a function of a single variable. Plots of the bicoherence at the pump frequency, with the power spectrum overlaid, are a convenient presentation format for PDI data (see Figs. 4, 5 and 6). The techniques and tools introduced here, and applied to probe data from a representative handful of shots, are currently being used to revisit a larger, more complete NSTX HHFW-heating data set. The findings from the comprehensive analysis will be presented elsewhere, once completed.

PDI during HHFW heating in NSTX has been identified before based on second-order (power spectrum) spectral analysis alone²⁻⁴. The earlier results were obtained at lower magnetic field (with edge majority-ion cyclotron frequency of 2 MHz), and in the absence of NBI, in both deuterium and helium plasmas. Up to three lower sidebands (at 28, 26 and 24 MHz, respectively) were shown²⁻⁴ and up to two low-frequency modes (at 2 and 4 MHz, respectively)⁴, but no upper sidebands. A more detailed comparison with both theory and these earlier experimental results will be performed and presented in a future publication.

ACKNOWLEDGMENTS

The work presented here was funded by PPPL Subcontract S014474-U.

REFERENCES

- ¹Ono M 1995 Physics of Plasmas **2** 4075–4082
- ²Wilson J R, Bernabei S, Biewer T, Diem S, Hosea J, LeBlanc B, Phillips C K, Ryan P and Swain D W 2005 *AIP Conference Proceedings* **787** 66–73
- ³Biewer T, Bell R, Diem S, Phillips C, Wilson J and Ryan P 2005 *Physics of Plasmas* **12** 056108
- ⁴Wilgen J, Ryan P, Hanson G, Swain D, Bernabei S, Greenough N, DePasquale S, Phillips C, Hosea J and Wilson J 2006 *Review of scientific instruments* **77** 10E933
- ⁵Oosako T, Takase Y, Ejiri A, Nagashima Y, Adachi Y, Kasahara H, Yamada T, Watanabe O, Tojo H, Kainaga S *et al.* 2009 *Nuclear Fusion* **49** 065020
- ⁶Porkolab M 1990 Fusion Engineering and Design **12** 93–103
- ⁷Kim Y C and Powers E J 1979 *IEEE Transactions on Plasma Science* 7 120–131
- ⁸Lagoutte D, Lefeuvre F and Hanasz J 1989 Journal of Geophysical Research **94** 435–442
- ⁹Shats M and Solomon W 2002 Physical Review Letters 88 045001
- ¹⁰Xu G S, Wan B N and Song M 2002 Physics of Plasmas **9** 150–154
- ¹¹Xu G, Wan B, Song M and Li J 2003 Physical Review Letters **91** 125001
- ¹²Nagashima Y, Hoshino K, Ejiri A, Shinohara K, Takase Y, Tsuzuki K, Uehara K, Kawashima H, Ogawa H, Ido T et al. 2005 Physical Review Letters **95** 095002
- ¹³Nagashima Y, Itoh K, Itoh S I, Hoshino K, Fujisawa A, Ejiri A, Takase Y, Yagi M, Shinohara K, Uehara K, Kusama Y and JFT-2M group 2006 *Plasma Physics and Controlled Fusion* 48 A377
- ¹⁴Crocker N, Peebles W, Kubota S, Fredrickson E, Kaye S, LeBlanc B and Menard J 2006 Physical Review Letters 97 045002
- ¹⁵Crocker N, Fredrickson E, Kubota S, Peebles W, Bell R, Kaye S, LeBlanc B and Menard J 2009 Physics of Plasmas 16 042513
- ¹⁶de Meijere C, Coda S, Krämer-Flecken A, Soldatov S, Albergante M et al. 2012 Plasma Physics and Controlled Fusion 54 105024



Princeton Plasma Physics Laboratory Office of Reports and Publications

Managed by Princeton University

under contract with the U.S. Department of Energy (DE-AC02-09CH11466)

P.O. Box 451, Princeton, NJ 08543 Phone: 609-243-2245 Fax: 609-243-2751 E-mail: <u>publications@pppl.gov</u> Website: <u>http://www.pppl.gov</u>